

Full Shade
原色

Reduction with Titanium Dioxide(1:2)
用钛白粉 (1:2) 冲淡色

U02



U03



U04



U06



U08



U08MX



Note: The actual color is based on the samples we sent you. This color shade is only for your reference.
注意: 本色卡仅供客户参考之用, 确切的颜色以我公司提供的样品为准。

Ultramarine Blue advantages and characteristics:

Compatible and suitable for all kinds of polymers

Maintains dimensional stability: non-warping/non-shrinking

Non-Toxic

Excellent heat resistance (up to 350°C, 10min)

Does not migrate

Excellent weather resistance

主要特征和性能:

适用于各种聚合物

保持尺寸稳定, 无翘曲变形

无毒

极佳的耐热性 (350°C, 10分钟内不变色)

无迁移

卓越的耐候性

| 型号 Grade | 水溶物 [N] Water Soluble Content [%] | 筛余物 @ 0.045mm [N] Sieve Residue (0.045mm) [%] | PH值 PH | | 含硫量 [%] Free Sulfur [%] | 105°C挥发物 [%] 105°C Moisture [%] | 吸油量 [g/100g] Oil Absorption [g/100g] | | 相对着色强度 [%] Relative tinting strength [%] | |
|-------------|---|---|--------------|--------------|----------------------------|------------------------------------|---|--------------|---|--------------|
| | 最大 % 最大 % | 最大 % 最大 % | 最小 % 最小 % | 最大 % 最大 % | 最大 % 最大 % | 最大 % 最大 % | 最小 % 最小 % | 最大 % 最大 % | 最小 % 最小 % | 最大 % 最大 % |
| U02 | 1.5 | 0.5 | 7.5 | 10 | 0.3 | 1.0 | 25.0 | 45.0 | 95 | 105 |
| U03 | 1.5 | 0.1 | 7.5 | 10 | 0.15 | 1.0 | 25.0 | 45.0 | 95 | 105 |
| U04 | 1.5 | 0.1 | 7.5 | 10 | 0.10 | 1.0 | 25.0 | 45.0 | 95 | 105 |
| U06 | 1.5 | 0.1 | 7.5 | 10 | 0.10 | 1.0 | 25.0 | 45.0 | 95 | 105 |
| U08 | 1.5 | 0.1 | 7.5 | 10 | 0.10 | 1.0 | 25.0 | 45.0 | 95 | 105 |
| U08MX | 1.5 | 0.1 | 7.5 | 10 | 0.10 | 1.0 | 25.0 | 45.0 | 95 | 105 |

This product meets ISO 788:1974(Ultramarine pigments for paints), it could be widely used in range of plastics, rubber, paints, coatings, soap, detergent powder, artist pigments, inks and papers.

本品符合ISO 788:1974标准(油漆用群青颜料), 广泛使用于塑料, 橡胶, 油漆, 涂料, 肥皂, 洗衣粉, 画家用颜料, 墨水和纸张等行业。

Package and Storage:

Packed in color kraft bag with 25kg net weight. Keep storing in dry and ventilated places, avoided from moisture, acid & alkali. Period of validity for one year. Your special package also could be supplied.

包装和储存:

牛皮纸复合袋, 每袋净重25公斤。储存于干燥通风处, 严禁与酸碱物品接触, 未拆开包装的有效期一年。可以按客户要求协议包装形式包装。